

乙烯-醋酸乙烯共聚物

Ethylene-VinylAcetate

Copolymers V2825

TDS NO.:JSPC/EVA-010.006-2018

特性

V2825 是一种乙烯-醋酸乙烯酯共聚物，具有很多优异特性，包括：柔软性与弹性特佳，粘着性优异，耐低温性良好，相容性良好，长期加温不致劣化，以及卫生无毒等。

Characterics

V2825 is an EVA copolymer which possesses super characteristics, included: flexibility and elasticity, excellent adhesion, good low temperature resistance, good compatibility, thermal stability and non-toxicity.

应用

1. 光伏产品

Applications

1. Photovoltaic products

物理性质 Physical Properties

项 目 Properties	试 验 方 法 Test Method	数 值 Typical Value
VA 含量 VA Content (%)	GB/T30925-2014	28
熔融指数 Melt Index (g/10min)	Q3207 JSPC EVA052	25
断裂强度 (模片) Tensile Strength at Break (kg/ cm ²)	GB/T 1040-2006	37
断裂伸长率 Tensile Elongaton at Break (%)	GB/T 1040-2006	800
维卡软化温度 Vicat Softening Point(℃)	GB/T1633-2000	40
熔点 Melt Point (℃)	GB/T19466-2004	71
密度 Density (g/cm ³)	GB/T1636-2008	0.948
透光率 Foreign Matter (个/kg)	GB/T 2410	94

以上信息真实准确，由于使用条件超出我们的控制范围，用户使用的所有风险都由用户承担，本公司恕不负责。

The information contained herein is, to our best knowledge, true and accurate. However, since conditions of use are beyond our control, all risks of such use are assumed by users.

JiangSu Sailboat Petrochemical Co.,Ltd. 江苏斯尔邦石化有限公司

Tel:886-0518-87516888 Fax:886-2-26599599 Web:www.shenghongpec.com Email:service_usi@shenghongpec.com

Address:Xuwei New Area, Lianyungang, Jiangsu, Province, China. 地址: 江苏省连云港市徐圩新区港前大道